

TABLA DE MEDIDAS Y PESOS

 WEIGHT AND DIMENSIONS - TABLEAU DES
 POIDS ET DIMENSIONS - GRÖÖE UND GEWICHTE

PACKING ONE

FORMATO / SIZE / FORMAT / FORMAT	25x25 mm / 1 "x1 "
ESPESOR / THICKNESS / EPAISSEUR / STÄRKE	~ 4,5 mm / 0.177 "
MEDIDAS HOJAS / SHEETS SIZE / DIMENSION PLAQUES / ABMESSUNG DER BLÄTTER	311x467 mm / 12.24 "x18.38 "
JUNTA / JOINT / JOINT / ABMESSUNG DER FUGE	~ 1.5 mm / 0.02 "
PESO / WEIGHT / POIDS / GEWICHT	1,31 kg /m² / 2.88 lb
CANTIDAD POR CAJA / QUANTITY PER BOX / QUANTITE PER CARTON / QUANTITÄT PRO KARTON	2,03 m² / 21.85 sqft
CAJAS POR PALLET / CARTONS PER PALLET / CARTONS PER PALETTE / KARTONS PRO PALETTE	60
PESO PALET / PALLET WEIGHT / POIDS PALETTE / PALETTENGewicht	1098 kg / 2420.67 lb

CARACTERÍSTICAS TÉCNICAS

 TEST DATA - CARACTÉRISTIQUES TECHNIQUES
 TECHNISCHE EIGENSCHAFTEN

 UNE EN ISO 10545 (13) **resistente / resistant / résistant / beständig**

 RESISTENCIA A LOS AGENTES QUÍMICOS
 RESISTANCE TO CHEMICAL AGENTS
 RESISTANCE AUX PRODUITS CHIMIQUES
 SAURE - UND LAUGHENBESTÄNDIGKEIT

 UNE EN ISO 10545 (9) **resistente / resistant / résistant / beständig**

 RESISTENCIA A LOS CAMBIOS DE TEMPERATURA
 RESISTANCE TO THERMAL SHOCKS
 RESISTANCE AUX CHOCS THERMIQUES
 TEMPERATURWECHSELBESTÄNDIGKEIT

 UNE EN ISO 10545 (12) **resistente / resistant / résistant / beständig**

 RESISTENCIA AL HIELO
 FROST RESISTANT
 RESISTANCE AU GEL
 FROSTBESTÄNDIGKEIT

 DIN 51094 **resistente / resistant / résistant / beständig**

 RESISTENCIA DE LOS COLORES A LA LUZ
 COLOURS RESISTANCE TO FADING
 RESISTANCE DES COULEURS A LA LUMIERE
 FARBBESTÄNDIGKEIT

 UNE EN ISO 10545 (3) **nula / none / nulle / null**

 ABSORCIÓN DE AGUA
 WATER ABSORPTION
 ABSORPTION D'EAU
 WASSERAUFNAHME

 UNE EN ISO 10545 (3) **Clase 5**

 RESISTENCIA A LAS MANCHAS
 RESISTANCE TO STAINING
 RESISTANCE AUX TACHES
 FLECKENBESTÄNDIG

DCOF Wet Dynamic Coefficient of friction	SLIP Resistance wearing shoes	SLIP Resistance in bare feet	Anti skid coefficient suitable for outdoor use and swimming pools
-	-	-	-

TEST ASTM

TEST PERFORMED AND REQUIREMENTS	CONCLUSIONS
RANGE OF THICKNESS (ASTM C499)	PASSES
FACIAL DIMENSIONS (ASTM C499)	PASSES
WEDGING (ASTM C502)	PASSES
WATER ABSORPTION (ASTM C373)	PASSES
THERMAL SHOCKS (ASTM C484)	PASSES
BOND STRENGHT (ASTM C482)	PASSES
CRAZING (ASTM C424)	PASSES